

BP9

Low Ceiling Two Post Lifts
9,000 lbs. Capacity

Features:

- 2-stage symmetric arms
- Secondary lock system includes a spring actuated slack chain locking device
- Carriage latch system – engages every 3"
- Dual hydraulic cylinders
- Low profile adapter design
- Includes four (4) frame engaging truck adapters
- Adapter extensions included
- Powder coated finish
- Third-party Gold Certified

**Commercial Grade
for Low Ceilings**

**113" MINIMUM
CEILING HEIGHT
REQUIRED**



Model Shown:
FWD BP9113000BL
9,000 lbs. capacity

SPECIFICATIONS	BP9113000BL
Capacity	9,000 lbs. (4082kg.)
Overall Height	111-1/4" (2825mm)
Overall Width	138-1/2" (3517mm)
Max. Rise With Extensions	80-1/2" (2044mm)
Rise Without Extensions	72" (1828mm)
Drive Through Clearance	97-1/4" (2470mm)
Width Inside Column	111" (2819mm)
Arm Reach (Min./Max.)	30" (762mm) / 46-1/4" (1174mm)
Min. Adapter Height	4-1/2" (114mm)
Drive-Over Height	1-1/2" (38mm)
Voltage/Amps	208/230v, 20 amps
Motor	2 HP/1Ø
Min. Ceiling Height	113" (2870mm)

Specifications subject to change without notice or liability
The BP9 lift is certified by ALI (Automotive Lift Institute) to meet American National Standard

Low-Profile Threaded Adapter Design:

The BP9 features low-profile, oversized pads with multiple extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5"

