

# F-12

## HEAVY DUTY TWO POST LIFT 12,000 lbs. Capacity

### Features:

- 2-stage front and rear arms
- Hydraulic cylinders in each column:
  - Full stroke
  - Cylinder rod concealed inside carriage
- Extended height configurations available
- Overhead cable equalization
- Spring operated arm restraints disengage at floor level
- Includes adapter extensions and storage bracket
- Single point lock release
- Durable powder coat finish
- Warranty:
  - Five years structural, 18 month parts, and six months labor
- ALL certified



Shown:  
FWD F12N300BL  
12,000 lbs. capacity



### Low-Profile Adapter Design:

The F12 features low-profile, oversized pads with multiple extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5"



Forward Lift, a leading manufacturer of automotive lifting equipment, provides reliable lift systems for independent repair shops, car dealerships, body shops, national accounts, home enthusiasts, hobbyists, and heavy-duty truck facilities. Using 21st century design tools allows us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously cycle tested to exceed durability standards. All Forward products are proof load tested to 1½ times rated capacity! The combination of high quality products and service provides you with the very best value - while not compromising safety, functionality or durability.

| SPECIFICATIONS                    | F12N300(BL/RD)*   |
|-----------------------------------|---|
| CAPACITY                          | 12,000 lbs. (5443kg)  |
| MAXIMUM RISE                      | 77-1/2" (1968mm)<br>With 5" adapter extension   |
| ADJUSTABLE OVERALL HEIGHT OPTIONS | 166" (4216mm) Standard Height (F12N300)<br>178" (4521mm) Extended Max. Height (F12N301)<br>154" (3912mm) (F12N302)<br>143" (3632mm) (F12N303) |
| OVERALL WIDTH                     | 140" or optional 146" (3556/3708mm)   |
| DRIVE THROUGH CLEARANCE           | 102-3/4" or optional 108-3/4" (2609/2762mm)   |
| OVERHEAD SWITCH HEIGHT OPTIONS    | 160-1/8" (4067mm) Standard<br>172-1/8" (4524mm) Extended<br>148-1/8" (3762mm)<br>137-1/8" (3483mm)  |
| FRONT REACH (MIN/MAX)             | 35"/ 54" (889mm / 1372mm)   |
| REAR REACH (MIN/MAX)              | 35"/ 54" (889mm / 1372mm)   |
| MIN/MAX ADAPTER HEIGHT            | 4-3/4" (120mm) w/o adapter extension<br>9-3/4" (248mm) w/5" adapter extension   |
| WIDTH INSIDE COLUMNS              | 120-7/8" (3070mm) Adjustable<br>114-7/8" (2918mm) Standard  |
| VOLTAGE/AMPS                      | 208V/230V, 17 amps  |
| MOTOR/PHASE                       | 1ph/2HP/50Hz<br>1ph/2HP/60Hz  |
| CEILING HEIGHT REQUIRED           | 168" (4267mm)   |

\* Lifts available in blue and red  
Specifications subject to change without notice or liability.



ENGINEERED TO PERFORM. BUILT TO LAST.

996 Industrial Drive  
Madison, IN 47250

Phone: 800.423.1722

Fax: 812.273.7329

www.forwardlift.com



Lit# Forward 4Post\_CR18\_Cutsheet\_2018.08

©2018 Vehicle Service Group<sup>SM</sup>  
Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group<sup>SM</sup>, Dover and all other trademarks are property of Dover Corporation and its affiliates.

