

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.



LIGHT DUTY TWO POST LIFT 10,000 lbs. Capacity

FEATURES:

Symmetrical column design


Spot-Rite™ 3-stage front arm design - spot vehicles asymmetrically or symmetrically

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- **ALI Certified**

INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"

Spot-Rite™3-Stage Front Arm Design

accommodates vehicle spotting both symmetrically and asymmetrically. Position the vehicle doors in front of or behind the lift columns to prevent door damage andallow easy technician access!



Vehicle Placement

Symmetric Vehicle Placement



996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722



www.forwardlift.com 📑 📵 🕡 🕞



Fax: 812.273.7329



Min/Max adapter height

Width inside column

Voltage/ Amps

Motor/Phase

SPECIFICATIONS

Capacity

Overhead switch height 137-5/8" (3496mm)

Maximum rise

Overall Height

DP10AN400MBL/RD*

Overall Width 131" or optional 137" (3327mm/4380mm)

208V/230V, 17 amps

1ph/2HP/60Hz

144" (3658mm)

Drive through clearance 99" (2515mm) or optional 105" (2667mm)

Front reach (Min/Max) 23" / 44-3/8" (584mm/1127mm) Rear reach (Min/Max) 36" / 58" (914mm/1473mm)

76 -1/4" (1937mm) w/5" extension

3-3/4" (95mm) w/o adapter extension

8-3/4" (222mm) w/ 5" adapter extension

109" or optional 115" (2769mm/2921mm)

10,000 lbs. (4535kg)

Specifications subject to change without notice or liability.