

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

Drive-over ramps and side rails provide the width to support wider vehicles while approaching and exiting the lift.

LOW-RISE LIFT 7,000 lbs. Capacity





· Dual lifting cylinders provide the required power

• The TL07 comes with four 3" rubber blocks and four 1.5" rubber blocks for added height



SPECIFICATIONS

Overall Length

Overall Width

Width Between

Length of Pad

Outside Width

Collapsed Height

Voltage/Amps

Speed of Rise

RISE HIGH STEP

RISE MID STEP

RISE LOW STEP

RISE TALL PAD

Locking Leg Heights

of Platforms Horizontal Movement

Length of Platforms

Platforms

TL07111000BL/RD* TL10111000BL/RD*

10,000 lbs. (4535kg)

90-1/2" (2298mm)

78-1/2" (1993mm)

22-3/4" (577mm)

51-1/4" (1301mm)

22-3/4" (577mm)

70-3/4" (1797mm)

16" (406mm)

4" (101mm)

13-3/8" (339mm) 17-3/8" (441mm) 21-3/8" (542mm)

115V, 20 amps

30-5/16" (769mm)

28-5/16" (719mm)

26-5/16" (668mm)

24-3/4" (628mm)

23-1/4" (590mm)

21-3/4" (552mm)

40 seconds

7,000 lbs. (3175kg)

90-1/2" (2298mm)

78-1/2" (1993mm)

22-3/4" (577mm)

51-1/4" (1301mm)

70-3/4" (1797mm)

17" (431mm)

16" (406mm)

4" (101mm)

13-3/8" (339mm)

17-3/8" (441mm) 21-3/8" (542mm)

115V, 20 amps

24-3/4" (628mm)

40 seconds

N/A

N/A

RISE SHORT PAD 23-1/4" (590mm)



FEATURES:

- Dual lifting cylinders provide the required power
- The TL10 comes with four 3-position adapters, four (4) 3" rubber blocks and four (4) 1.5" rubber blocks for added height





996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329



www.forwardlift.com 📑 📵 🕡 🕞



