





FEATURES:

Symmetrical column design with 2-stage symmetric arms

- Carriage latch system - engages every 3"
- · Secondary lock system includes a spring actuated slack chain locking device
- · Dual hydraulic cylinders
- Powder coated finish
- · ALI Certified

INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



BP9113000BL/RD*

80-1/2" w/5" extension

208V/230V, 17 amps

9,000 lbs.

111-1/4"

138-1/2"

97-1/4"

30" / 46-1/4"

111'

4-1/2"

1-1/2"

113"

1ph/2HP

72"

The perfect lift for customers who have low ceilings.

The BP9's overall height means it will fit in any shop with at least a 10' ceiling height. BP stands for base plate indicated by the steel plate that run between the two columns of the lift protecting the cables that would normally run overhead on any other two-post lift.





ALI GOLD CERTIFIED

Forward Lift BP9 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.





Phone: 800.423.1722 Fax: 812.273.7329





*Lifts available in blue (BL) and red (RD) Specifications subject to change without notice or liability.

Height

SPECIFICATIONS

Capacity

Overall Height

Overall Width

Maximum Rise

Drive Through Clearance

Width Inside column

Minimum Adapter

Drive-over Height

Voltage/Amps

Motor/Phase

Arm Reach (Min/Max)

Ceiling Height Required