



FEATURES:

Symmetrical column design

2-stage front and rear arms

Four height configuration models for most ceiling heights

Adjustable width options

- Overhead cable equalization •
- Single point lock release •
- Includes adapter storage bracket
- Durable powder coated finish •
- **ALI** Certified

INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS 3 1/2" and 5"



SPECIFICATIONS	F12N300BL/RD*
Capacity	12,000 lbs.
Maximum Rise with 5" Extension	77 1/2"
Adjustable Overall Height Options	F12N300 13' 10" Standard F12N301 14' 10" Max. Height F12N302 12' 10" F12N303 11' 11"
Overall Width	11' 8" or optional 12' 2"
Drive-Thru	102 3/4" or optional 108 3/4"
Overhead Switch Height Options	F12N300 160 1/8" Standard F12N301 172 1/8" Extended F12N302 148 1/8" F12N303 137 1/8"
Front Arm Reach (Min/Max)	35" / 54"
Rear Arm Reach (Min/Max)	35" / 54"
Minimum Adapter Height	4 3/4"
Width Inside Columns	114 7/8" Standard 120 7/8" Optional
Voltage/Amps	208-230V, 17 amps

2HP / 1PH



ALI GOLD CERTIFIED

Lit# Forward F12 CUTSHEET.2023.05 ©2023 Vehicle Service Group® All rights reserved.

Forward Lift F12 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive Madison, IN 47250

Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates.

Phone: 800.423.1722 Fax: 812.273.7329



Motor/Phase *Lifts available in blue (BL) and red (RD)

Specifications subject to change without notice or liability.